



DoP-No. 1-1 0005

B

Aduro A/S, Hasselager Allè 13D, 8260 Viby J
www.adurofire.com

21

EN 16510-2-1:2022
NB-No. 1235
Aduro 1.1, 1.1 SK, 1.4

Room heater fired by solid fuel intended for installation in residential buildings.

Appliance for intermittent operation
Suitable for installation onto a shared flue systemMinimum distance to combustible materials

distance to the bottom	$D_B=0$ mm
distance to the floor in front	$D_F=0$ mm
distance to the ceiling	$D_C=750$ mm
distance to the rear	$D_R=100$ mm
distance to the side	$D_S=400$ mm
distance to the corner	$D_{S(C)}=100$ mm
distance to the side radiation area	$D_L=0$ mm
distance to adjacent combustible materials	$D_P=1000$ mm

Environmental values

CO- emission	≤ 1250 mg/m ³
NOx- emission	≤ 200 mg/m ³
OGC- emission	≤ 120 mg/m ³
Particulate matter emissions	≤ 30 mg/m ³

Performance

Flue gas outlet temperature	289 °C
Minimum flue draught	12 Pa
Space heat output	6 kW
Energy efficiency	80 %
Energy-Efficiency Index (EEI)	106
Energy-Efficiency class	A

Recommended fuel	Wood logs
Type of the appliance	Type B

Only use recommended fuels!
Please read and follow the user operating instructions before starting!

Production No.